

## Concrete Mould Oil

Product Name	Typical Properties				Large products			Small products			Boards		Structures			Characteristic · Application		
	Appearance	Color (ASTM)	Viscosity @40 mm <sup>2</sup> /s (cSt)	Flash Point	Sewerage pipe · U-shaped gutter	Wave-dissipating block	Caisson block	Pole · Hume pipe	Block · U-shaped gutter	Concrete tile	Railroad cross-tie	Face block	Slate	ALC panel	Dam exterior wall		Tunnel	Sewage line
CONCRETE MOULD OIL A	Light yellow, clear liquid	L0.5	3.1	65														Mould lubricant for railroad tie, general mould lubricant for concrete form.
CONCRETE MOULD OIL B	Yellow, clear liquid	L1.0	3.3	69														For moulding of steel form, compatible with concrete, with not severe condition during curing.
CONCRETE MOULD OIL E	Light yellow, clear liquid	L0.5	2.0	56														Mould lubricant for concrete form.
CONCRETE MOULD OIL L	Light yellow, clear liquid	L0.5	1.9	56														Designed for concrete block, roof tile, and U-shaped gutter moulding.
CONCRETE MOULD OIL E-1	Light yellow, clear liquid	L0.5	3.5	82														Concrete mould lubricant for general use.
CONCRETE MOULD OIL E-1(KAI)	Light yellow, translucent liquid	L0.5	3.2	79														Concrete mould lubricant for general use.
CONCRETE MOULD OIL MO(KAI)	Yellow, translucent liquid	L2.5	14.2	100														For use in enclosed spaces, such as tunnel, indoorplant. Low odor.
CONCRETE MOULD OIL TP	Yellow, translucent liquid	L1.0	5.6	54														Mould lubricant for general form. e.g. building, large construction, concrete block.
MOULD RIKEIZAI A	Brown, translucent liquid	L3.0	52.0	190														Mould lubricant for concrete form of ALC panels.
MOULD RIKEIZAI B	Brown, clear liquid	L3.5	132.7	274														Mould lubricant for concrete form of ALC panels.